

 Design to EN 50041 Lever angle adjustable in 10° steps Thermoplastic enclosure Double-insulated Good resistance to oil and petroleum spirit Wide range of alternative actuators Actuator heads can be repositioned by 4 x 90° 		Z4V3H 336-02Z-1583-2
 Thermoplastic enclosure Double-insulated Good resistance to oil and petroleum spirit Wide range of alternative actuators 		• Design to EN 50041
 NO IMAGE AVAILABLE Oouble-insulated Good resistance to oil and petroleum spirit Wide range of alternative actuators 		 Lever angle adjustable in 10° steps
NO IMAGE • Good resistance to oil and petroleum spirit AVAILABLE • Wide range of alternative actuators		Thermoplastic enclosure
AVAILABLE • Good resistance to oil and petroleum spirit • Wide range of alternative actuators	NO IMAGE	Double-insulated
-		 Good resistance to oil and petroleum spirit
 Actuator heads can be repositioned by 4 x 90° 		 Wide range of alternative actuators
		 Actuator heads can be repositioned by 4 x 90°
• 1 Cable entry M 20 x 1.5		• 1 Cable entry M 20 x 1.5

Schmersal India Pvt. Ltd., Plot No - G-7/1, Ranjangaon MIDC, Tal. - Shirur, Dist.- Pune 412 220 The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible. Generated on: 13/01/2025, 1:23 pm