



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO.: 2024010305669666

NAME AND ADDRESS OF THE APPLICANT

K.A. Schmersal GmbH & Co. KG
Moeddinghofe 30, D-42279 Wuppertal, Germany

NAME AND ADDRESS OF THE MANUFACTURER

K.A. Schmersal GmbH & Co. KG
Moeddinghofe 30, D-42279 Wuppertal, Germany

NAME AND LOCATION OF THE FACTORY

K.A. Schmersal GmbH & Co. KG
Im Ostpark 2, D-35435 Wettenberg, Germany

PRODUCT NAME,MODEL AND SPECIFICATION

Hinge Safety Switch
TESF... : Ui:250V(36V for ST24 types);Uimp:2.5kV(0.8 kV for ST24 types);Ith:2.5A;AC-15:Ue/Ie:230VAC/2A;DC-13:Ue/Ie:24VDC/1A(ST24 types);IP65 ;

STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB/T 14048.5-2017

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C03-02:2024).

Valid from: Aug.02,2024

Valid until: Aug.01,2029

The certificate information and validity could be checked by scanning the QR code below or logging in to the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).



SIGNATURE:

谢肇煦



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.





CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO. : 2024010305669666

Appendix : Page 1 of 1

Type description :

TESF (1)/(2)/(3)/(4)/(5)			
Nr.	Option	Description	描述
(1)	Blank	without Alignment aid for mounting	无限位
	A	with Alignment aid for mounting	有限位
(2)	Blank	with additional hinge	有附加铰链
	S	without additional hinge	无附加铰链
(3)	Blank	Screw connection	螺丝连接
	CC	Cage clamp connection	笼式接线夹
	ST24	Connector 24 V	24V 连接器
(4)	Blank	Standard type	标准类型
	.1	Connector bottom side *)	底部连接器 *)
	.2	Connector top side *)	顶部连接器 *)
	.1PE	Connector bottom side with ground connection *)	底部连接器带接地 *)
	.2PE	Connector top side with ground connection *)	顶部连接器带接地 *)
(5)	0	Preset for front assembly	预设在前部装配
	180	Preset for inside assembly	预设在内部分装配
	U	Adjustable on site	现场调节

*)Only for connector type 仅适用于连接器类型

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.